

SHOWER PAN

RENOVATIVE BATH SYSTEMS SUBMITTAL DATA

TOP VIEW



SIDE VIEW




Shower Pan

The shower enclosure shall be RBSP6030 SH 4.0 Pan, Left-Right Drain. Finished surface shall be of a sanitary-grade Polyester Gelcoat exibiting a minimal thickness of 15 dry mils, and a finished cured Barcol hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of molded reinforced fiberglass with a minimum fiberglass content. The unit shall have outside dimensions of 60" x 31" x 6". The gelcoat pan shall meet ANSI Z124.2, NAHB, UPC, comply with CSA, and shall meet the requirements of Southern Building Code.

- 1) 4.0" Threshold.
- 2) Available Left or Right Hand Drain Location.

FRONT VIEW



DUE TO THE NATURE OF THE MATERIALS INVOLVED UNIT DIMENSIONS MAY VARY $\pm~1/2~\text{INCH}$

Job Name:		RENOVATIVE BATH SYSTEMS	
	Drawing#: RBSP60	30 BF 1.0 Pan Left or Right Drain	
Date Approved:	Date: 3-31-09	Revised: 12-21-10	
Wholesaler:	Quote No.		
		Drawing#: RBSP60 Date Approved: Date: 3-31-09	